

Accessory Wheel Usage Matrix

O1SL, Cadillac CT6 - 20" Wheels

OEM Build Condition					Upsize Requirements and Restrictions				Re-Programming Required - Call TCSC/Techline			
Model Years	Make	Model	Series/Body Style	OEM Wheel Size	Accessory Wheel RPO	Approved Road Tires	Approved Usage	Install Tire Pressure Label	Electronic Brake Control Module	Engine Control Module (Speedometer)	Electronic Power Steering	Electronic Suspension Control Module
2019 to 2023	Cadillac	CT6	KHKJKL 69	18"/19"	SHH & 5JO	Goodyear Eagle Touring 245/40R20 95W AL3 GM PN: 84030956 RPOs: QP1 XBO TPC: 1471MS	APPROVED for use with LGX, LGW, LSY Engines NOT APPROVED with LTA Engine	Y - Configure Tire Pressure in BCM using GDS2	N	Y	N	N
2019 to 2023	Cadillac	CT6	KHKJKLKN 69	18"/19"	5JW	Goodyear Eagle Touring 245/40R20 95W AL3 GM PN: 84030956 RPOs: QP1 XBO TPC: 1471MS	APPROVED for All Engines	Y - Configure Tire Pressure in BCM using GDS2	N	Y	N	N
2019 to 2023	Cadillac	CT6	KHKJKL 69	20"	SHH, 5JO, and 5JW	Reuse Production Tire	APPROVED for use with 5EH/QP1 Tires	N - Do NOT replace tire placard label	N	N	N	N

Notes

- Installer must call GM Techline Customer Support Center (TCSC) at (800) 828-6860 to set up module re-programming, prior to initiating a programming event.
- TCSC Note: When searching for calibrations in GPDS/APM, leave UPC prefix blank to search all prefixes
- Check eSI for most up to date version of Usage Matrix

DRE NOTES:

Update Areas in RED

Add additional columns as necessary

When complete, review in Accessory Integration meeting and move to Final folder on Sharepoint

Print Usage Chart at PDF, load into eSI, and inform John Yadlosky of new chart with link.