

Accessory Tire Usage Chart

T1xx Silverado/Sierra MY20- 22" AT Tire

OEM Build Condition					Upsize Requirements and Restrictions				Engine Control Module (Speedometer) (FNA 6506B)
Model Years	Make	Model	Series/Body Style	OEM Tire Size	Approved Road Tires	Approved Usage	Jack	Install Tire Pressure Label	
2020	Chevrolet/GMC	Silverado/Sierra	CK 105 43 CK 107 43/53	17"/18"	Bridgestone Dueler A/T P285/45R22 110H GM Part#: 19190768 RPOs: XAH and RHH TPC: 2349	Approved for use with: all suspension pkgs: Z71, Z85, Z7X, Z60, Z45 Not approved w/Regular Cab; Not approved with NHT (towing) or VYU (snow plow prep)	Jack ASM PN 84617951 is required for vehicles that are upsizing from 17"/18" tires to a 22" tire; EXCEPT if truck has Z7X/SG3 (lifted suspension)	Y - Configure Tire Pressure in BCM using GDS2	Y
2020	Chevrolet/GMC	Silverado/Sierra	CK 105 43 CK 107 43/53	20"	Bridgestone Dueler A/T P285/45R22 110H GM Part#: 19190768 RPOs: XAH and RHH TPC: 2349	Approved for use with: all suspension pkgs: Z71, Z85, Z7X, Z60, Z45 Not approved w/Regular Cab; Not approved with NHT (towing) or VYU (snow plow prep)	No change required	Y - Configure Tire Pressure in BCM using GDS2	Y

Notes

- Installer must call GM Techline Customer Support Center (TCSC) at (800) 828-6860 to set up module re-programming, prior to initiating a programming event.
- TCSC Note: When searching for calibrations in GPDS/APM, leave UPC prefix blank to search all prefixes
- Check eSI for most up to date version of Usage Matrix